

AM9d-24W : AM9d-24W-6000K-IP44-90D-P

Mirror Light, 24W, 12000lm, 220-240VAC, 6000K, 90°, IP44,
Dim.965X60X40mm.



GENERAL PRODUCT DATA

Product Category	AM9d-24W,
Technical Description	Mirror Light, 24W, 1680lm, 220-240VAC, 6000K, 90°, IP44, Dim.965X60X40mm.
Mounting Type	
Color	Chrome

LIGHT TECHNICAL DATA

Light Source	
Lum Flux (LM)	1680lm
Lighting Efficiency (lm/W)	70
CCT	6000K
CRI	
CRI(Optional)	
MacAdam Step	Mac Adam Step 5
MacAdam Step (On request)	
Beam Angle	

POLAR DIAGRAM

ELECTRICAL PRODUCT DATA

Wattage (w)	
Voltage Range (V)	220-240VAC
Frequency	50/60Hz
Driver	Non-Dimmable
Dimming(Optional 1)	
Dimming(Optional 2)	

MECHANICAL DATA

Material	
Dimensions	
Cut out	
IP	44
IK	
Operating temperature	-25~+45°C
Product weight	

LED LIFESPAN

Led Lifespan	
--------------	--

DIMENSIONAL DRAWING



● THINK LIGHT

FOR MORE INFORMATION PLEASE CONTACT

Lucio Lighting B.V

www.lucio-international.com
info@lucio-international.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).
We reserve the right to make technical changes.