

## LED Spot Light : S52a-13W-3000K-IP20-24D-P

LED Spot Light(White + White),13W,1300lm,Ra>80,220-240VAC,3000K,24°,IP20,Dia. 90x115.5mm



### GENERAL PRODUCT DATA

Product Category	LED Spot Light,
Technical Description	LED Spot Light(White + White),13W,1300lm,Ra>80,220-240VAC,3000K,24°,IP20,Dia. 90x115.5mm
Mounting Type	Recessed
Color	White + White

### LIGHT TECHNICAL DATA

Light Source	COB
Lum Flux (LM)	1300
Lighting Efficiency (lm/W)	100
CCT	3000K
CRI	Ra>80
CRI(Optional)	Ra>90
MacAdam Step	Mac Adam Step 3
MacAdam Step (On request)	Mac Adam Step 2
Beam Angle	24°

### POLAR DIAGRAM

### ELECTRICAL PRODUCT DATA

Wattage (w)	13
Voltage Range (V)	220-240VAC
Frequency	50/60Hz
Driver	Non-Dimmable
Dimming(Optional 1)	DALI
Dimming(Optional 2)	0-10V Dimming

### MECHANICAL DATA

Material	Aluminum
Dimensions	Dia. 90x115.5mm
Cut out	Dia.80mm
IP	20
IK	
Operating temperature	-20~+40°C
Product weight	

### LED LIFESPAN

Led Lifespan	> 50,000 Hours
--------------	----------------

### DIMENSIONAL DRAWING



● THINK LIGHT

FOR MORE INFORMATION PLEASE CONTACT

Lucio Lighting B.V

[www.lucio-international.com](http://www.lucio-international.com)  
[info@lucio-international.com](mailto:info@lucio-international.com)

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process. Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121). We reserve the right to make technical changes.