

DR22e-20W : DR22e-20W-5000K-IP20-15D-P

LED Downlight, 20W, 1800lm, Ra>80, 220-240VAC, 5000K, 15°, IP20, Ø98X129mm




GENERAL PRODUCT DATA

Product Category	DR22e-20W,
Technical Description	LED Downlight, 20W, 1800lm, Ra>80, 220-240VAC, 5000K, 15°, IP20, Ø98X129mm
Mounting Type	Recessed
Color	White

LIGHT TECHNICAL DATA

Light Source	COB
Lum Flux (LM)	1800
Lighting Efficiency (lm/W)	90
CCT	5000K
CRI	Ra>80
CRI(Optional)	Ra>90
MacAdam Step	<3
MacAdam Step (On request)	
Beam Angle	15°

POLAR DIAGRAM



ELECTRICAL PRODUCT DATA

Wattage (w)	20
Voltage Range (V)	220-240VAC
Frequency	50/60Hz
Driver	Non-Dimmable
Dimming(Optional 1)	DALI
Dimming(Optional 2)	1-10V Dimming


MECHANICAL DATA

Material	Aluminium Die-cast
Dimensions	Ø98X129mm
Cut out	Ø100mm.
IP	20
IK	02
Operating temperature	-20~+40°C
Product weight	

LED LIFESPAN

Led Lifespan	> 50,000 hours
--------------	----------------

DIMENSIONAL DRAWING



● THINK LIGHT

FOR MORE INFORMATION PLEASE CONTACT

Lucio Lighting B.V

www.lucio-international.com
info@lucio-international.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process. Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121). We reserve the right to make technical changes.