

LED Spot Light : G14a-30W-3000K-IP40-36D-P

LED Linear Recessed, 30W, 3000lm, Ra>80, 220-240VAC, 3000K, 36°, IP20, 410X45X55mm.



GENERAL PRODUCT DATA

Product Category	LED Spot Light,
Technical Description	LED Linear Recessed, 30W, 3000lm, Ra>80, 220-240VAC, 3000K, 36°, IP20, 410X45X55mm.
Mounting Type	Recessed
Color	White + Black

LIGHT TECHNICAL DATA

Light Source	SMD
Lum Flux (LM)	3000
Lighting Efficiency (lm/W)	100
CCT	3000K
CRI	Ra>80
CRI(Optional)	Ra>90
MacAdam Step	
MacAdam Step (On request)	
Beam Angle	36°

POLAR DIAGRAM

ELECTRICAL PRODUCT DATA

Wattage (w)	30
Voltage Range (V)	220-240VAC
Frequency	50/60Hz
Driver	Non-Dimming
Dimming(Optional 1)	DALI
Dimming(Optional 2)	1-10 Dimming

MECHANICAL DATA

Material	Aluminium
Dimensions	410X45X55mm.
Cut out	395X40x50mm.
IP	40
IK	
Operating temperature	-20~+40°C
Product weight	

LED LIFESPAN

Led Lifespan	>50,000 Hours
--------------	---------------

DIMENSIONAL DRAWING



● THINK LIGHT

FOR MORE INFORMATION PLEASE CONTACT

Lucio Lighting B.V

www.lucio-international.com
info@lucio-international.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.