

DR27c-20W-4000K-IP20-36D-E

LED Downlight, 20W, lm, Ra>80, 220-240VAC, 4000K, 36°, IP20, ø145x102mm




GENERAL PRODUCT DATA

Product Category	
Technical Description	LED Downlight, 20W, lm, Ra>80, 220-240VAC, 4000K, 36°, IP20, ø145x102mm
Mounting Type	Recessed
Color	White

LIGHT TECHNICAL DATA

Light Source	COB
Lum Flux (LM)	1970
Lighting Efficiency (lm/W)	98.5
CCT	4000K
CRI	Ra>80
CRI(Optional)	Ra>90
MacAdam Step	<4
MacAdam Step (On request)	
Beam Angle	36°

POLAR DIAGRAM



ELECTRICAL PRODUCT DATA

Wattage (w)	20
Voltage Range (V)	220-240VAC
Frequency	50/60Hz
Driver	Non Dimming
Dimming(Optional 1)	DALI
Dimming(Optional 2)	1-10 Dimming


MECHANICAL DATA

Material	Die-Cast Aluminum
Dimensions	ø145x102mm
Cut out	ø125mm
IP	20
IK	02
Operating temperature	-20~+40°C
Product weight	0.570Kg

LED LIFESPAN

Led Lifespan	> 50,000 Hours
--------------	----------------

DIMENSIONAL DRAWING



● THINK LIGHT

FOR MORE INFORMATION PLEASE CONTACT

Lucio Lighting B.V

www.lucio-international.com
info@lucio-international.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).
We reserve the right to make technical changes.