

AR75c-40W : AR75c-40W-6000K-IP40-120-P

Architectural Series, LED Pendant
Light,40W,3600lm,Ra>80,220-
240VAC,6000K,120°,IP40,Ø580x15 mm




GENERAL PRODUCT DATA

Product Category	AR75c-40W,
Technical Description	Architectural Series, LED Pendant Light,40W,3600lm,Ra>80,220- 240VAC,6000K,120°,IP40,Ø580x15 mm
Mounting Type	Suspended
Color	White

LIGHT TECHNICAL DATA

Light Source	SMD
Lum Flux (LM)	3600
Lighting Efficiency (lm/W)	90
CCT	6000K
CRI	Ra>80
CRI(Optional)	Ra>90
MacAdam Step	<3
MacAdam Step (On request)	
Beam Angle	120°

POLAR DIAGRAM



ELECTRICAL PRODUCT DATA

Wattage (w)	40
Voltage Range (V)	220-240VAC
Frequency	50/60Hz
Driver	Non Dimming
Dimming(Optional 1)	
Dimming(Optional 2)	1-10 Dimming


MECHANICAL DATA

Material	Aluminium
Dimensions	Ø580x15 mm
Cut out	
IP	40
IK	
Operating temperature	-20~+40°C
Product weight	

LED LIFESPAN

Led Lifespan	> 50,000 Hours
--------------	----------------

DIMENSIONAL DRAWING



● THINK LIGHT

FOR MORE INFORMATION PLEASE CONTACT

Lucio Lighting B.V

www.lucio-international.com
info@lucio-international.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).
We reserve the right to make technical changes.