

HB1d-120W : HB1d-120W-4000K-IP65-30x70D-P

LED Highbay,120W,16200lm,Ra>70,100-
240VAC,4000K,30°x70°,IP65,948x137x102mm




GENERAL PRODUCT DATA

Product	HB1d-120W,
Category	
Technical Description	LED Highbay,120W,16200lm,Ra>70,100- 240VAC,4000K,30°x70°,IP65,948x137x102mm
Mounting Type	Suspended
Color	BLACK

LIGHT TECHNICAL DATA

Light Source	SMD
Lum Flux (LM)	16200lm
Lighting Efficiency (lm/W)	135
CCT	4000K
CRI	Ra>70
CRI(Optional)	Ra>80
MacAdam Step	Mac Adam Step 3
MacAdam Step (On request)	0
Beam Angle	30°x70°

POLAR DIAGRAM



ELECTRICAL PRODUCT DATA

Wattage (w)	120
Voltage Range (V)	100-240VAC
Frequency	50/60Hz
Driver	Non-Dimmable
Dimming(Optional 1)	DALI
Dimming(Optional 2)	1-10 Dimming


MECHANICAL DATA

Material	Aluminum Alloy
Dimensions	948x137x102mm
Cut out	
IP	65
IK	
Operating temperature	-30~+50°C
Product weight	

LED LIFESPAN

Led Lifespan	> 50,000 Hours
--------------	----------------

DIMENSIONAL DRAWING



● THINK LIGHT

FOR MORE INFORMATION PLEASE CONTACT

Lucio Lighting B.V

www.lucio-international.com
info@lucio-international.com

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).
We reserve the right to make technical changes.